

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Trade name : 1000FS-B
 Product code : 1000FS-B
 Other means of identification : 1000FS-B/55, 1000FS-B/5, 1000FS-B/1, 1000FS-B/P

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Protective Industrial Polymers
 7875 Bliss Parkway
 North Ridgeville, Ohio 44039 - USA-Ohio
 T 440-327-0015
www.protectpoly.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 800-424-9300 (Outside USA) 703-527-3887.

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Acute toxicity (oral) Category 4	H302	Harmful if swallowed
Skin corrosion/irritation Category 1A	H314	Causes severe skin burns and eye damage

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H302 - Harmful if swallowed
 H314 - Causes severe skin burns and eye damage

Precautionary statements (GHS-US) : P260 - Do not breathe vapors
 P264 - Wash hands thoroughly after handling
 P270 - Do not eat, drink or smoke when using this product
 P280 - Wear protective clothing
 P301+P312 - If swallowed: Call a doctor if you feel unwell
 P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting
 P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
 P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
 P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P310 - Immediately call a doctor
 P321 - Specific treatment (see a doctor if symptoms do not go away. on this label)
 P330 - Rinse mouth
 P363 - Wash contaminated clothing before reuse
 P405 - Store locked up
 P501 - Dispose of contents/container to in accordance with local regulations

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

1000FS-B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
4-tert-butylphenol	(CAS No) 98-54-4	24.15 - 35	Skin Irrit. 2, H315 Eye Dam. 1, H318
(1,6-Hexanediamine,C,C,C-trimethyl-)	(CAS No) 25620-58-0	17.25 - 31.05	Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314
1,3-bis(aminomethyl)benzene	(CAS No) 1477-55-0	13.8 - 25	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1A, H314
Phenol,4-nonyl-,branched	(CAS No) 84852-15-3	10 - 15	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2-methyl-1,5-pentanediamine	(CAS No) 15520-10-2	0 - 5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314
Benzenemethanol	(CAS No) 100-51-6	0 - 5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2A, H319 Aquatic Acute 2, H401
2,4,6-tris(dimethylaminomethyl)phenol	(CAS No) 90-72-2	0 - 5	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315
4-(2,4-dimethylheptan-3-yl)phenol	(CAS No) 25154-52-3	0.69 - 3.45	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : Call a physician immediately.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
- First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/injuries after skin contact : Burns.
- Symptoms/injuries after eye contact : Serious damage to eyes.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Alcohol resistant foam, water, water fog, CO2, dry chemical, dry sand, limestone powder.

5.2. Specific hazards arising from the chemical

- Fire hazard : Heating may cause a fire.
- Explosion hazard : No direct explosion hazard.
- Reactivity : Stable under normal conditions.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

1000FS-B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe vapors. Wear personal protective equipment.
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.
Incompatible products : Epoxy resins under controlled conditions.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Benzenemethanol (100-51-6)

Not applicable

2-methyl-1,5-pentanediamine (15520-10-2)

Not applicable

4-tert-butylphenol (98-54-4)

Not applicable

1,3-bis(aminomethyl)benzene (1477-55-0)

ACGIH	Local name	m-Xylene α,α' -diamine
ACGIH	ACGIH Ceiling (mg/m ³)	0.1 mg/m ³ (m-Xylene alfa,alfa'-diamine; USA; Momentary value; TLV - Adopted Value)
ACGIH	Remark (ACGIH)	Eye, skin, & GI irr

2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)

Not applicable

Phenol,4-nonyl-,branched (84852-15-3)

Not applicable

(1,6-Hexanediamine,C,C,C-trimethyl-) (25620-58-0)

Not applicable

4-(2,4-dimethylheptan-3-yl)phenol (25154-52-3)

Not applicable

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

1000FS-B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.3. Individual protection measures/Personal protective equipment

Hand protection:

protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Light yellow
Odor	: Ammonical
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: <
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions.

10.2. Chemical stability

can react strongly with epoxy resins at elevated temperatures.

10.3. Possibility of hazardous reactions

Will not occur.

10.4. Conditions to avoid

Open flame. Heat.

10.5. Incompatible materials

No additional information available

1000FS-B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide. Nitrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed.
(Conclusive but not sufficient for classification)

1000FS-B	
ATE US (oral)	500 mg/kg body weight
Benzenemethanol (100-51-6)	
LD50 oral rat	1620 mg/kg (Rat; Experimental value)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit, Inconclusive, insufficient data, Dermal)
LC50 inhalation rat (mg/l)	> 4.178 mg/l air (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol))
ATE US (oral)	1620 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
2-methyl-1,5-pentanediamine (15520-10-2)	
LD50 oral rat	1690 mg/kg (Rat)
ATE US (oral)	1690 mg/kg body weight
4-tert-butylphenol (98-54-4)	
LD50 oral rat	> 2000 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LC50 inhalation rat (mg/l)	> 5.6 mg/l/4h (Rat; Experimental value)
ATE US (oral)	3370 mg/kg body weight
ATE US (dermal)	2621 mg/kg body weight
1,3-bis(aminomethyl)benzene (1477-55-0)	
LD50 oral rat	930 mg/kg (Rat)
LD50 dermal rabbit	2000 mg/kg (Rabbit)
LC50 inhalation rat (mg/l)	2.4 mg/l/4h (Rat)
ATE US (oral)	930 mg/kg body weight
ATE US (dermal)	2000 mg/kg body weight
ATE US (vapors)	2.4 mg/l/4h
ATE US (dust, mist)	2.4 mg/l/4h
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
LD50 oral rat	2169 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
ATE US (oral)	1200 mg/kg body weight
Phenol,4-nonyl-,branched (84852-15-3)	
LD50 oral rat	1412 mg/kg body weight (Other, Rat, Male / female, Experimental value, Oral)
ATE US (oral)	1412 mg/kg body weight
(1,6-Hexanediamine,C,C,C-trimethyl-) (25620-58-0)	
LD50 oral rat	910 mg/kg (Rat, Literature study, Oral)
ATE US (oral)	500 mg/kg body weight
4-(2,4-dimethylheptan-3-yl)phenol (25154-52-3)	
ATE US (oral)	500 mg/kg body weight

Skin corrosion/irritation : Causes severe skin burns and eye damage.
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
(Based on available data, the classification criteria are not met)
Carcinogenicity : Not classified
(Based on available data, the classification criteria are not met)

1000FS-B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
Specific target organ toxicity – single exposure	: Not classified (Based on available data, the classification criteria are not met)
Specific target organ toxicity – repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
Symptoms/injuries after skin contact	: Burns.
Symptoms/injuries after eye contact	: Serious damage to eyes.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

Benzenemethanol (100-51-6)	
LC50 fish 1	460 mg/l (EPA OPP 72-1, 96 h, Pimephales promelas, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 Daphnia 1	230 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Fresh water, Experimental value, GLP)
ErC50 (algae)	770 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
2-methyl-1,5-pentanediamine (15520-10-2)	
LC50 fish 1	130 mg/l (LC50; 48 h)
4-tert-butylphenol (98-54-4)	
EC50 Daphnia 1	3.9 mg/l (EC50; 48 h)
LC50 fish 2	5.14 mg/l (LC50; 96 h)
Threshold limit algae 2	11.2 mg/l (EC50; 72 h)
1,3-bis(aminomethyl)benzene (1477-55-0)	
EC50 Daphnia 1	16 mg/l (EC50; 48 h)
LC50 fish 2	> 100 mg/l (LC50; 96 h)
Threshold limit algae 1	12 mg/l (EC50; 72 h)
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
LC50 fish 1	175 mg/l (APHA, 96 h, Cyprinus carpio, Static system, Fresh water, Experimental value, Nominal concentration)
ErC50 (algae)	84 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, GLP)
Phenol,4-nonyl-,branched (84852-15-3)	
LC50 fish 1	0.08 mg/l (ASTM E729-96, 96 h, Hybopsis monacha, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 Daphnia 1	0.084 mg/l (ASTM E729-88, 48 h, Daphnia magna, Semi-static system, Fresh water, Experimental value)
(1,6-Hexanediamine,C,C,C-trimethyl-) (25620-58-0)	
LC50 fish 1	172 mg/l (48 h, Leuciscus idus, Static system, Literature study)
EC50 Daphnia 1	31.5 mg/l (24 h, Daphnia magna, Literature study)

12.2. Persistence and degradability

1000FS-B	
Persistence and degradability	Not established.

1000FS-B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Benzenemethanol (100-51-6)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.6 g O ₂ /g substance
Chemical oxygen demand (COD)	2.4 g O ₂ /g substance
ThOD	2.5 g O ₂ /g substance
2-methyl-1,5-pentanediamine (15520-10-2)	
Persistence and degradability	Biodegradability in water: no data available.
4-tert-butylphenol (98-54-4)	
Persistence and degradability	Readily biodegradable in water. Low potential for mobility in soil. Photolysis in the air.
ThOD	2.77 g O ₂ /g substance
1,3-bis(aminomethyl)benzene (1477-55-0)	
Persistence and degradability	Not readily biodegradable in water.
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Persistence and degradability	Not readily biodegradable in water.
Phenol,4-nonyl-,branched (84852-15-3)	
Persistence and degradability	Biodegradability in soil: no data available. Readily biodegradable in water.
(1,6-Hexanediamine,C,C,C-trimethyl-) (25620-58-0)	
Persistence and degradability	Not readily biodegradable in water.

12.3. Bioaccumulative potential

Benzenemethanol (100-51-6)	
Log Pow	1 - 1.1 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
2-methyl-1,5-pentanediamine (15520-10-2)	
Log Pow	0.27 (Estimated value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
4-tert-butylphenol (98-54-4)	
BCF fish 1	120 (BCF; 3 h)
BCF fish 2	20 - 88 (BCF)
BCF other aquatic organisms 1	34 (BCF; 24 h; Chlorella sp.)
BCF other aquatic organisms 2	240 (BCF; 5 h; Bacteria)
Log Pow	3 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method; 23 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
1,3-bis(aminomethyl)benzene (1477-55-0)	
BCF fish 1	< 2.7 (BCF)
Log Pow	0.15
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Log Pow	-0.66 (Experimental value, EPA OPPTS 830.7550: Partition Coefficient (n-octanol/water), Shake Flask Method, 21.5 °C)
Bioaccumulative potential	Not bioaccumulative.
Phenol,4-nonyl-,branched (84852-15-3)	
BCF fish 1	1200 - 1300 (OECD 305: Bioconcentration: Flow-Through Fish Test, 16 day(s), Gasterosteus aculeatus, Flow-through system, Salt water, Experimental value, Fresh weight)
Log Pow	5.4 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 23 °C)
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).
(1,6-Hexanediamine,C,C,C-trimethyl-) (25620-58-0)	
Log Pow	0.7 (Literature)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

1000FS-B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.4. Mobility in soil

Benzenemethanol (100-51-6)	
Surface tension	39 mN/m (20 °C)
Ecology - soil	No (test)data on mobility of the substance available.
4-tert-butylphenol (98-54-4)	
Log Koc	log Koc,3.1; QSAR
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Log Koc	1.32 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.
Phenol,4-nonyl-,branched (84852-15-3)	
Log Koc	4.35 - 5.69 (log Koc, Other, Experimental value, GLP)
Ecology - soil	Adsorbs into the soil.
(1,6-Hexanediamine,C,C,C-trimethyl-) (25620-58-0)	
Ecology - soil	No (test)data on mobility of the substance available.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Contain and dispose of waste according to local regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1760 Corrosive liquids, n.o.s. (1,3-bis(aminomethyl)benzene), 8, III
UN-No.(DOT) : UN1760
Proper Shipping Name (DOT) : Corrosive liquids, n.o.s.
1,3-bis(aminomethyl)benzene
Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136
Packing group (DOT) : III - Minor Danger
Hazard labels (DOT) : 8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 241
DOT Symbols : G - Identifies PSN requiring a technical name

1000FS-B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	: IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 154
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
Other information	: No supplementary information available.

TDG

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

1000FS-B

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Benzenemethanol (100-51-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

2-methyl-1,5-pentanediamine (15520-10-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

4-tert-butylphenol (98-54-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

1,3-bis(aminomethyl)benzene (1477-55-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Phenol,4-nonyl-,branched (84852-15-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

(1,6-Hexanediamine,C,C,C-trimethyl-) (25620-58-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

4-(2,4-dimethylheptan-3-yl)phenol (25154-52-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

1000FS-B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

No additional information available

Phenol,4-nonyl-,branched (84852-15-3)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

1,3-bis(aminomethyl)benzene (1477-55-0)

U.S. - New Jersey - Right to Know Hazardous Substance List

(1,6-Hexanediamine,C,C,C-trimethyl-) (25620-58-0)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Other information : Disclaimer: This SDS to the best of our knowledge conforms to the requirements of OSHA 20 CFR 1910.1200 and summarizes the health and safety hazard information and general guidance on how to safely handle the material at the date of issue. Each user must review the SDS in the context of how the product will be handled and used in the workplace.

Full text of H-phrases:

H227	Combustible liquid
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product