

### SECTION 1: Identification

#### 1.1. Identification

Product form	: Mixture
Product name	: 1800-B
Product code	: 1800-B
Other means of identification	: 1800-B/1, 1800-B/5, 1800-B/55

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Protective Industrial Polymers  
7875 Bliss Parkway  
North Ridgeville, Ohio 44039 - USA-Ohio  
T 440-327-0015  
[www.protectpoly.com](http://www.protectpoly.com)

#### 1.4. Emergency telephone number

Emergency number : Chemtrec: 800427-9300 (Outside USA) 703-527-3887

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Acute toxicity (oral), Category 4	H302
Skin corrosion/irritation, Category 1A	H314
Sensitisation — Skin, Category 1	H317
Specific target organ toxicity — Single exposure, Category 2	H371

Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US)	: Danger
Contains	: Benzenemethanol; (4,4'-diaminodicyclohexyl)methane; 4-(2,4-dimethylheptan-3-yl)phenol; 2,4,6-tris(dimethylaminomethyl)phenol
Hazard statements (GHS-US)	: H302 - Harmful if swallowed H314 - Causes severe skin burns and eye damage H317 - May cause an allergic skin reaction H371 - May cause damage to organs (Skin) (Skin)
Precautionary statements (GHS-US)	: P260 - Do not breathe vapours P261 - Avoid breathing vapours P264 - Wash hands, forearms and face thoroughly after handling P270 - Do not eat, drink or smoke when using this product P272 - Contaminated work clothing must not be allowed out of the workplace P280 - Wear protective clothing P301+P312 - If swallowed: Call a doctor if symptoms persist. if you feel unwell P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting P302+P352 - If on skin: Wash with plenty of soap, water P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P310 - Immediately call a doctor if symptoms persist P321 - Specific treatment (see a doctor if symptoms do not go away. on this label)

# 1800-B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P330 - Rinse mouth  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention  
P363 - Wash contaminated clothing before reuse  
P405 - Store locked up  
P501 - Dispose of contents/container to in accordance with local regulations

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
4-(2,4-dimethylheptan-3-yl)phenol	(CAS No) 25154-52-3	25 - 35	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
O,O'-Bis(2-aminopropyl)polypropyleneglycol	(CAS No) 9046-10-0	15 - 25	Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
Xylene Formaldehyde Resin	(CAS No) 26139-75-3	10 - 20	Skin Irrit. 2, H315
(4,4'-diaminodicyclohexyl)methane	(CAS No) 1761-71-3	5 - 15	Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314 Skin Sens. 1B, H317 STOT SE 2, H371 Aquatic Acute 2, H401
Benzenemethanol	(CAS No) 100-51-6	0 - 5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H302 Eye Irrit. 2A, H319 Aquatic Acute 2, H401
2,4,6-tris(dimethylaminomethyl)phenol	(CAS No) 90-72-2	0 - 5	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.  
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.  
First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after skin contact : Burns. May cause an allergic skin reaction.  
Symptoms/injuries after eye contact : Serious damage to eyes.  
Symptoms/injuries after ingestion : Burns.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

# 1800-B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Do not breathe vapours. Avoid contact with skin and eyes.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Do not breathe vapours. Avoid contact with skin and eyes. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Benzenemethanol (100-51-6)

Not applicable

##### O,O'-Bis(2-aminopropyl)polypropyleneglycol (9046-10-0)

Not applicable

##### (4,4'-diaminodicyclohexyl)methane (1761-71-3)

Not applicable

##### 4-(2,4-dimethylheptan-3-yl)phenol (25154-52-3)

Not applicable

##### 2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)

Not applicable

##### Xylene Formaldehyde Resin (26139-75-3)

Not applicable

#### 8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Hand protection : Protective gloves.

Eye protection : Safety glasses.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.

Environmental exposure controls : Avoid release to the environment.

# 1800-B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: straw colored liquid
Odour	: Ammonical Amine-like
Odour threshold	: No data available
pH	: Alkaline
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: > 430 °F
Flash point	: > 303 °F
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Vapour pressure	: < 2 mbar
Relative density	: No data available
Relative vapour density at 20 °C	: No data available
Solubility	: Water: Solubility in water of component(s) of the mixture : • Benzenemethanol: 4.4 g/100ml (50 °C) • (4,4'-diaminodicyclohexyl)methane: 1.23 g/100ml (20 °C) • 2,4,6-tris(dimethylaminomethyl)phenol: > 16 g/100ml
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

#### 9.2. Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

#### 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed.

#### 1800-B

ATE US (oral)	910.207 mg/kg bodyweight
---------------	--------------------------

# 1800-B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Benzenemethanol (100-51-6)</b>	
LD50 oral rat	1620 mg/kg (Rat; Experimental value)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit; Inconclusive, insufficient data)
ATE US (oral)	1620.000 mg/kg bodyweight
ATE US (gases)	4500.000 ppmv/4h
ATE US (vapours)	11.000 mg/l/4h
ATE US (dust,mist)	1.500 mg/l/4h

<b>(4,4'-diaminodicyclohexyl)methane (1761-71-3)</b>	
LD50 oral rat	625 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LD50 dermal rabbit	2110 mg/kg bodyweight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity)
ATE US (oral)	625.000 mg/kg bodyweight
ATE US (dermal)	2110.000 mg/kg bodyweight

<b>4-(2,4-dimethylheptan-3-yl)phenol (25154-52-3)</b>	
ATE US (oral)	500.000 mg/kg bodyweight

<b>2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)</b>	
LD50 oral rat	1200 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; 2169 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rat	> 2000 mg/kg (Rat; Literature study; Other; >1 ml/kg; Rat; Experimental value)
ATE US (oral)	1200.000 mg/kg bodyweight

Skin corrosion/irritation : Causes severe skin burns and eye damage.

pH: Alkaline

Serious eye damage/irritation : Not classified

pH: Alkaline

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause damage to organs (Skin) (Skin).

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Symptoms/injuries after skin contact : Burns. May cause an allergic skin reaction.

Symptoms/injuries after eye contact : Serious damage to eyes.

Symptoms/injuries after ingestion : Burns.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

<b>Benzenemethanol (100-51-6)</b>	
LC50 fish 1	460 mg/l (LC50; EPA OPP 72-1; 96 h; Pimephales promelas; Static system; Fresh water; Experimental value)

<b>(4,4'-diaminodicyclohexyl)methane (1761-71-3)</b>	
EC50 Daphnia 2	6.84 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
Threshold limit algae 1	141.42-200,ErC50; DIN 38412-9; 72 h; Desmodesmus subspicatus; Static system; Fresh water; Experimental value
Threshold limit algae 2	141.42-200,EbC50; DIN 38412-9; 72 h; Desmodesmus subspicatus; Static system; Fresh water; Experimental value

# 1800-B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)</b>	
EC50 Daphnia 2	41.3 mg/l (LC50; 48 h; Daphnia magna)
Threshold limit algae 2	84 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Scenedesmus subspicatus; Static system; Fresh water; Experimental value)

### 12.2. Persistence and degradability

<b>Benzenemethanol (100-51-6)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. No (test) data on mobility of the substance available.
Biochemical oxygen demand (BOD)	1.6 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.4 g O <sub>2</sub> /g substance
ThOD	2.5 g O <sub>2</sub> /g substance

<b>(4,4'-diaminodicyclohexyl)methane (1761-71-3)</b>	
Persistence and degradability	Not readily biodegradable in water. Low potential for adsorption in soil. Photolysis in the air.

<b>2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)</b>	
Persistence and degradability	Not readily biodegradable in water. Highly mobile in soil. Low potential for adsorption in soil.

### 12.3. Bioaccumulative potential

<b>Benzenemethanol (100-51-6)</b>	
Log Pow	1-1.1, Experimental value; Other; 20 °C
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

<b>(4,4'-diaminodicyclohexyl)methane (1761-71-3)</b>	
BCF fish 1	<= <=6<60,BCF; OECD 305: Bioconcentration: Flow-Through Fish Test; 4 weeks; Cyprinus carpio; Flow-through system; Fresh water; Read-across
Log Pow	2.03 - 3.26 (2.03; Experimental value; OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

<b>2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)</b>	
Log Pow	0.77 (Literature; 0.219; Experimental value; Equivalent or similar to OECD 107; 21.5 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

### 12.4. Mobility in soil

<b>Benzenemethanol (100-51-6)</b>	
Surface tension	0.04 N/m (20 °C)

<b>(4,4'-diaminodicyclohexyl)methane (1761-71-3)</b>	
Log Koc	Koc, SRC PCKOCWIN v2.0; 103.1; Calculated value; log Koc; SRC PCKOCWIN v2.0; 2.0132; Calculated value

<b>2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)</b>	
Log Koc	Koc, SRC PCKOCWIN v2.0; 20.98; QSAR; log Koc; 1.32; Calculated value

### 12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

### Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN2735 Amines, liquid, corrosive, n.o.s., 8, III

# 1800-B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

UN-No.(DOT) : UN2735  
Proper Shipping Name (DOT) : Amines, liquid, corrosive, n.o.s.  
Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136  
Hazard labels (DOT) : 8 - Corrosive



Packing group (DOT) : III - Minor Danger  
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203  
DOT Packaging Bulk (49 CFR 173.xxx) : 241  
DOT Symbols : G - Identifies PSN requiring a technical name  
DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672)  
T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / (1 + a (tr - tf))$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling  
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP  
DOT Packaging Exceptions (49 CFR 173.xxx) : 154  
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L  
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L  
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel  
DOT Vessel Stowage Other : 52 - Stow "separated from" acids  
Other information : No supplementary information available.

### TDG

No additional information available

### Transport by sea

No additional information available

### Air transport

No additional information available

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### 1800-B

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Benzenemethanol (100-51-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### O,O'-Bis(2-aminopropyl)polypropyleneglycol (9046-10-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### (4,4'-diaminodicyclohexyl)methane (1761-71-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### 4-(2,4-dimethylheptan-3-yl)phenol (25154-52-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

# 1800-B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### Xylene Formaldehyde Resin (26139-75-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

## 15.2. International regulations

### CANADA

No additional information available

### EU-Regulations

No additional information available

### National regulations

No additional information available

## 15.3. US State regulations

No additional information available

## SECTION 16: Other information

### Other information

: Disclaimer: This SDS to the best of our knowledge conforms to the requirements of OSHA 20 CFR 1910.1200 and summarizes the health and safety hazard information and general guidance on how to safely handle the material at the date of issue. Each user must review the SDS in the context of how the product will be handled and used in the workplace.

### Full text of H-statements:

H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H371	May cause damage to organs
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

### NFPA health hazard


: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.

### NFPA fire hazard

: 1 - Must be preheated before ignition can occur.

### NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



### HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

# 1800-B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*