

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Product name : TLE-B
 Product code : TLE-B
 Other means of identification : TLE-B/Q

1.2. Relevant identified uses of the substance or mixture and uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Protective Industrial Polymers
 7875 Bliss Parkway
 North Ridgeville, Ohio 44039 - USA-Ohio
 T 440-327-0015
www.protectpoly.com

1.4. Emergency telephone number

Emergency number : Chemtrec: 800427-9300 (Outside USA) 703-527-3887

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Acute toxicity (oral), Category 4 H302
 Skin corrosion/irritation, Category 1A H314

Full text of H statements : see section 16

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS05

GHS07

Signal word (GHS-US) :

Danger

Contains :

2-methyl-1,5-pentanediamine; Benzenemethanol; 1,3-bis(aminomethyl)benzene; (1,6-Hexanediamine,C,C,C-trimethyl-); 4-(2,4-dimethylheptan-3-yl)phenol; 2,4,6-tris(dimethylaminomethyl)phenol; Phenol,4-nonyl-,branched

Hazard statements (GHS-US) :

H302 - Harmful if swallowed
 H314 - Causes severe skin burns and eye damage

Precautionary statements (GHS-US) :

P260 - Do not breathe vapours
 P264 - Wash hands thoroughly after handling
 P270 - Do not eat, drink or smoke when using this product
 P280 - Wear protective clothing
 P301+P312 - If swallowed: Call a doctor if you feel unwell
 P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting
 P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
 P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
 P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P310 - Immediately call a doctor
 P321 - Specific treatment (see a doctor if symptoms do not go away. on this label)
 P330 - Rinse mouth
 P363 - Wash contaminated clothing before reuse
 P405 - Store locked up
 P501 - Dispose of contents/container to in accordance with local regulations

TLE-B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
4-tert-butylphenol	(CAS No) 98-54-4	24.15 - 35	Skin Irrit. 2, H315 Eye Dam. 1, H318
(1,6-Hexanediamine,C,C,C-trimethyl-)	(CAS No) 25620-58-0	17.25 - 31.05	Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314
1,3-bis(aminomethyl)benzene	(CAS No) 1477-55-0	13.8 - 25	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1A, H314
Phenol,4-nonyl-,branched	(CAS No) 84852-15-3	10 - 15	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2-methyl-1,5-pentanediamine	(CAS No) 15520-10-2	0 - 5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314
Benzenemethanol	(CAS No) 100-51-6	0 - 5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2A, H319 Aquatic Acute 2, H401
2,4,6-tris(dimethylaminomethyl)phenol	(CAS No) 90-72-2	0 - 5	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315
4-(2,4-dimethylheptan-3-yl)phenol	(CAS No) 25154-52-3	0.69 - 3.45	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after skin contact	: Burns.
Symptoms/injuries after eye contact	: Serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Alcohol resistant foam, water, water fog, CO2, dry chemical, dry sand, limestone powder.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Heating may cause a fire.
Explosion hazard	: No direct explosion hazard.
Reactivity	: Stable under normal conditions.

TLE-B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe vapours. Wear personal protective equipment.
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.
Incompatible products : Epoxy resins under controlled conditions.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Benzenemethanol (100-51-6)		
Not applicable		
2-methyl-1,5-pentanediamine (15520-10-2)		
Not applicable		
4-tert-butylphenol (98-54-4)		
Not applicable		
1,3-bis(aminomethyl)benzene (1477-55-0)		
ACGIH	ACGIH Ceiling (mg/m ³)	0.1 mg/m ³ (m-Xylene alfa, alfa'-diamine; USA; Momentary value; TLV - Adopted Value)
ACGIH	Remark (ACGIH)	Eye, skin, & GI irr
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)		
Not applicable		
Phenol,4-nonyl-,branched (84852-15-3)		
Not applicable		
(1,6-Hexanediamine,C,C,C-trimethyl-) (25620-58-0)		
Not applicable		
4-(2,4-dimethylheptan-3-yl)phenol (25154-52-3)		
Not applicable		

TLE-B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Hand protection	: protective gloves.
Eye protection	: Safety glasses.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment.
Environmental exposure controls	: Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Light yellow
Odour	: Ammonical
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: <
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Vapour pressure	: No data available
Relative density	: No data available
Relative vapour density at 20 °C	: No data available
Solubility	: Water: Solubility in water of component(s) of the mixture : • 2-methyl-1,5-pentanediamine: Complete • Benzenemethanol: 4.4 g/100ml (50 °C) • 4-tert-butylphenol: 0.06 g/100ml (25 °C, insoluble) • 1,3-bis(aminomethyl)benzene: Complete • 2,4,6-tris(dimethylaminomethyl)phenol: > 16 g/100ml • Phenol,4-nonyl-,branched: 5.7 mg/l (25 °C, insoluble)
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions.

10.2. Chemical stability

can react strongly with epoxy resins at elevated temperatures.

10.3. Possibility of hazardous reactions

Will not occur.

10.4. Conditions to avoid

Open flame. Heat.

10.5. Incompatible materials

No additional information available

TLE-B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide. Nitrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed.
(Conclusive but not sufficient for classification)

TLE-B	
ATE US (oral)	500.000 mg/kg bodyweight
Benzenemethanol (100-51-6)	
LD50 oral rat	1620 mg/kg (Rat; Experimental value)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit; Inconclusive, insufficient data)
ATE US (oral)	1620.000 mg/kg bodyweight
ATE US (gases)	4500.000 ppmv/4h
ATE US (vapours)	11.000 mg/l/4h
ATE US (dust,mist)	1.500 mg/l/4h
2-methyl-1,5-pentanediamine (15520-10-2)	
LD50 oral rat	1690 mg/kg (Rat)
ATE US (oral)	1690.000 mg/kg bodyweight
4-tert-butylphenol (98-54-4)	
LD50 oral rat	> 2000 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LC50 inhalation rat (mg/l)	> 5.6 mg/l/4h (Rat; Experimental value)
ATE US (oral)	3370.000 mg/kg bodyweight
ATE US (dermal)	2621.000 mg/kg bodyweight
1,3-bis(aminomethyl)benzene (1477-55-0)	
LD50 oral rat	930 mg/kg (Rat)
LD50 dermal rabbit	2000 mg/kg (Rabbit)
LC50 inhalation rat (mg/l)	2.4 mg/l/4h (Rat)
ATE US (oral)	930.000 mg/kg bodyweight
ATE US (dermal)	2000.000 mg/kg bodyweight
ATE US (vapours)	2.400 mg/l/4h
ATE US (dust,mist)	2.400 mg/l/4h
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
LD50 oral rat	1200 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; 2169 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rat	> 2000 mg/kg (Rat; Literature study; Other; >1 ml/kg; Rat; Experimental value)
ATE US (oral)	1200.000 mg/kg bodyweight
Phenol,4-nonyl-,branched (84852-15-3)	
LD50 oral rat	1882 mg/kg (Rat; Other; Experimental value; 1412 mg/kg bodyweight; Rat; Experimental value)
ATE US (oral)	1882.000 mg/kg bodyweight
ATE US (dermal)	2040.000 mg/kg bodyweight
(1,6-Hexanediamine,C,C,C-trimethyl-) (25620-58-0)	
LD50 oral rat	< 910 mg/kg (Rat; Literature study)
ATE US (oral)	500.000 mg/kg bodyweight
4-(2,4-dimethylheptan-3-yl)phenol (25154-52-3)	
ATE US (oral)	500.000 mg/kg bodyweight

Skin corrosion/irritation : Causes severe skin burns and eye damage.
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
(Based on available data, the classification criteria are not met)

TLE-B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
Specific target organ toxicity (single exposure)	: Not classified (Based on available data, the classification criteria are not met)
Specific target organ toxicity (repeated exposure)	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
Symptoms/injuries after skin contact	: Burns.
Symptoms/injuries after eye contact	: Serious damage to eyes.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

Benzenemethanol (100-51-6)	
LC50 fish 1	460 mg/l (LC50; EPA OPP 72-1; 96 h; Pimephales promelas; Static system; Fresh water; Experimental value)
2-methyl-1,5-pentanediamine (15520-10-2)	
LC50 fish 1	130 mg/l (LC50; 48 h)
4-tert-butylphenol (98-54-4)	
EC50 Daphnia 1	3.9 mg/l (EC50; 48 h)
LC50 fish 2	5.14 mg/l (LC50; 96 h)
Threshold limit algae 2	11.2 mg/l (EC50; 72 h)
1,3-bis(aminomethyl)benzene (1477-55-0)	
EC50 Daphnia 1	16 mg/l (EC50; 48 h)
LC50 fish 2	> 100 mg/l (LC50; 96 h)
Threshold limit algae 1	12 mg/l (EC50; 72 h)
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
EC50 Daphnia 2	41.3 mg/l (LC50; 48 h; Daphnia magna)
Threshold limit algae 2	84 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Scenedesmus subspicatus; Static system; Fresh water; Experimental value)
Phenol,4-nonyl-,branched (84852-15-3)	
EC50 Daphnia 2	0.085 mg/l (EC50; ASTM E729-88; 48 h; Daphnia magna; Semi-static system; Fresh water; Experimental value)
Threshold limit algae 2	0.027 mg/l (EC50; EPA OTS 797.1050; 96 h; Skeletonema costatum; Static system; Salt water; Experimental value)
(1,6-Hexanediamine,C,C,C-trimethyl-) (25620-58-0)	
LC50 fish 1	172 mg/l (LC50; 48 h; Leuciscus idus; Static system)
EC50 Daphnia 1	31.5 mg/l (EC50; 24 h; Daphnia magna)
Threshold limit algae 1	29.5 mg/l (EC50; 72 h; Scenedesmus subspicatus)

12.2. Persistence and degradability

TLE-B	
Persistence and degradability	Not established.
Benzenemethanol (100-51-6)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. No (test) data on mobility of the substance available.

TLE-B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Benzenemethanol (100-51-6)	
Biochemical oxygen demand (BOD)	1.6 g O ₂ /g substance
Chemical oxygen demand (COD)	2.4 g O ₂ /g substance
ThOD	2.5 g O ₂ /g substance
2-methyl-1,5-pentanediamine (15520-10-2)	
Persistence and degradability	Biodegradability in water: no data available.
4-tert-butylphenol (98-54-4)	
Persistence and degradability	Readily biodegradable in water. Low potential for mobility in soil. Photolysis in the air.
ThOD	2.77 g O ₂ /g substance
1,3-bis(aminomethyl)benzene (1477-55-0)	
Persistence and degradability	Not readily biodegradable in water.
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Persistence and degradability	Not readily biodegradable in water. Highly mobile in soil. Low potential for adsorption in soil.
Phenol,4-nonyl-,branched (84852-15-3)	
Persistence and degradability	Inherently biodegradable. Biodegradability in soil: no data available. Adsorbs into the soil. Photodegradation in the air.
(1,6-Hexanediamine,C,C,C-trimethyl-) (25620-58-0)	
Persistence and degradability	Not readily biodegradable in water. No (test)data on mobility of the substance available. Photodegradation in the air.

12.3. Bioaccumulative potential

Benzenemethanol (100-51-6)	
Log Pow	1-1.1, Experimental value; Other; 20 °C
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
2-methyl-1,5-pentanediamine (15520-10-2)	
Log Pow	0.27 (Estimated value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
4-tert-butylphenol (98-54-4)	
BCF fish 1	120 (BCF; 3 h)
BCF fish 2	20 - 88 (BCF)
BCF other aquatic organisms 1	34 (BCF; 24 h; Chlorella sp.)
BCF other aquatic organisms 2	240 (BCF; 5 h; Bacteria)
Log Pow	3 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method; 23 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
1,3-bis(aminomethyl)benzene (1477-55-0)	
BCF fish 1	< 2.7 (BCF)
Log Pow	0.15
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Log Pow	0.77 (Literature; 0.219; Experimental value; Equivalent or similar to OECD 107; 21.5 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Phenol,4-nonyl-,branched (84852-15-3)	
BCF fish 1	271 (BCF; 480 h; Pimephales promelas)
BCF fish 2	1200/1300,BCF; OECD 305: Bioconcentration: Flow-Through Fish Test; 32 days; Gasterosteus aculeatus; Flow-through system; Salt water; Experimental value; Fresh weight
Log Pow	3.28 (OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method; 5.4; Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method; 23 °C)
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).
(1,6-Hexanediamine,C,C,C-trimethyl-) (25620-58-0)	
Log Pow	0.7 (Literature)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

TLE-B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.4. Mobility in soil

Benzenemethanol (100-51-6)	
Surface tension	0.04 N/m (20 °C)
4-tert-butylphenol (98-54-4)	
Log Koc	log Koc,3.1; QSAR
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Log Koc	Koc,SRC PCKOCWIN v2.0; 20.98; QSAR; log Koc; 1.32; Calculated value
Phenol,4-nonyl-,branched (84852-15-3)	
Log Koc	log Koc,Other; >= 4.35 - <= 5.69; Experimental value; GLP

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Contain and dispose of waste according to local regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1760 Corrosive liquids, n.o.s. (1,3-bis(aminomethyl)benzene), 8, III

UN-No.(DOT) : UN1760

Proper Shipping Name (DOT) : Corrosive liquids, n.o.s.
1,3-bis(aminomethyl)benzene

Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Hazard labels (DOT) : 8 - Corrosive



Packing group (DOT) : III - Minor Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 241

DOT Symbols : G - Identifies PSN requiring a technical name

DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672)

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / (1 + a (tr - tf))$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling

TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP

DOT Packaging Exceptions (49 CFR 173.xxx) : 154

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel

TLE-B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"
Other information : No supplementary information available.

TDG

No additional information available

Transport by sea

UN-No. (IMDG) : ----- TO BE COMPLETED/CALCULATED -----

Air transport

UN-No. (IATA) : ----- TO BE COMPLETED/CALCULATED -----

SECTION 15: Regulatory information

15.1. US Federal regulations

TLE-B

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Benzenemethanol (100-51-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

2-methyl-1,5-pentanediamine (15520-10-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

4-tert-butylphenol (98-54-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

1,3-bis(aminomethyl)benzene (1477-55-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Phenol,4-nonyl-,branched (84852-15-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

(1,6-Hexanediamine,C,C,C-trimethyl-) (25620-58-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

4-(2,4-dimethylheptan-3-yl)phenol (25154-52-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

1,3-bis(aminomethyl)benzene (1477-55-0)

U.S. - New Jersey - Right to Know Hazardous Substance List

(1,6-Hexanediamine,C,C,C-trimethyl-) (25620-58-0)

U.S. - New Jersey - Right to Know Hazardous Substance List

TLE-B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information

Other information

: Disclaimer: This SDS to the best of our knowledge conforms to the requirements of OSHA 20 CFR 1910.1200 and summarizes the health and safety hazard information and general guidance on how to safely handle the material at the date of issue. Each user must review the SDS in the context of how the product will be handled and used in the workplace.

Full text of H-statements:

H227	Combustible liquid
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product